

| <b>General</b>                                       |   |
|--|---|
| Product type   | Internal power distribution boards                      |
| Types of components                                  | ProCube   |
| Product abbreviations                                | PC.W-D  |
| Product designation                                  | All types of construction objects and plants            |
| Inlet type   | Cable inlet   |
| Output type  | Cable output  |
| Purpose  | Stationary  |
| Protection rating                                    | IP43  |
| <b>Indicators</b>                                    |   |
| Number of phases                                     | 3 phases  |
| Rated frequency                                      | 50hz  |
| U - current voltage                                  | 400/230B  |
| I - Rated secondary current A                        | 16-125A   |
| Output   | PC.W-MRD load breakers, 30-100mA Differential automatic |
| Meter  | Possible to install 2-6 meters                          |
| Icu short-circuit breaking current (peak value) [kA] | 4.5-10kA  |
| Thickness  | Frame-160mm<br>Panel-130mm                              |
| Width  | Frame-950mm<br>Panel-860mm                              |
| Height   | Frame-975mm<br>Panel-920mm                              |
| <b>Additional</b>                                    |   |
| Standard   | ISO9001:2015, MNS 5834:2008                             |
| Ambient temperature of use                           | -50°C...+50°C   |
| Ambient temperature of storage                       | -40°C...+50°C   |