

| | |
|------------------------------------------------------|----------------------------------------------|
| General | |
| Product type | Internal power distribution boards |
| Types of components | ProCube |
| Product abbreviations | PC.W |
| Product designation | All types of construction objects and plants |
| Inlet type | Cable inlet |
| Output type | Cable output |
| Purpose | Stationary |
| Protection rating | IP43 |
| Indicators | |
| Number of phases | 3 phases |
| Rated frequency | 50hz |
| U - current voltage | 400/230B |
| I Rated secondary current A | 16-250A |
| P current power | 10-150kV |
| Owning module | 16-32M |
| Icu short-circuit breaking current (peak value) [kA] | 4.5-40kA |
| Automatic breaker type | MCB; MCCB |
| Thickness | 250mm |
| Width | 660mm |
| Height | 1250mm |
| Additional | |
| Standard | ISO9001:2015, MNS 5834:2008 |
| Ambient temperature of use | -50°C...+50°C |
| Ambient temperature of storage | -40°C...+50°C |

| General | |
|------------------------------------------------------|----------------------------------------------|
| Product type | Internal power distribution boards |
| Types of components | ProCube |
| Product abbreviations | PC.WX |
| Product designation | All types of construction objects and plants |
| Inlet type | Cable inlet |
| Output type | Cable output |
| Purpose | Stationary and concealed |
| Protection rating | IP43 |
| Indicators | |
| Number of phases | 3 phases |
| Rated frequency | 50hz |
| U-current voltage | 400/230B |
| I-Rated secondary current A | 16-250A |
| P-current power | 10-150kBm |
| Owning module | 16-24M |
| Icu short-circuit breaking current (peak value) [kA] | 4.5-40kA |
| Automatic breaker type | MCB; MCCB |
| Thickness | Panel-190mm Frame-150mm |
| Width | Panel-655mm Frame-610mm |
| Height | Panel-1120mm Frame-1050mm |
| Additional | |
| Standard | ISO9001:2015, MNS 5834:2008 |
| Ambient temperature of use | -50°C...+50°C |
| Ambient temperature of storage | -40°C...+50°C |