

General	
Product type	Internal power distribution boards
Types of components	ProCube
Product abbreviations	PC.W
Product designation	All types of construction objects and plants
Inlet type	Cable inlet
Output type	Cable output
Purpose	Stationary
Protection rating	IP43
Indicators	
Number of phases	3 phases
Rated frequency	50hz
U - current voltage	400/230B
I Rated secondary current A	16-250A
P current power	10-150kV
Owning module	16-32M
Icu short-circuit breaking current (peak value) [kA]	4.5-40kA
Automatic breaker type	MCB; MCCB
Thickness	250mm, 300mm
Width	660mm
Height	1650mm
Additional	
Standard	ISO9001:2015, MNS 5834:2008
Ambient temperature of use	-50°C...+50°C
Ambient temperature of storage	-40°C...+50°C

General	
Product type	Internal power distribution boards
Types of components	ProCube
Product abbreviations	PC.WX
Product designation	All types of construction objects and plants
Inlet type	Cable inlet
Output type	Cable output
Purpose	Stationary and concealed
Protection rating	IP43
Indicators	
Number of phases	3 phases
Rated frequency	50hz
U-current voltage	400/230B
I-Rated secondary current A	16-250A
P-current power	10-150kBm
Owning module	16-24M
Icu short-circuit breaking current (peak value) [kA]	4.5-40kA
Automatic breaker type	MCB; MCCB
Thickness	Panel-190mm Frame-150mm
Width	Panel-655mm Frame-610mm
Height	Panel-1520mm Frame-1450mm
Additional	
Standard	ISO9001:2015, MNS 5834:2008
Ambient temperature of use	-50°C...+50°C
Ambient temperature of storage	-40°C...+50°C