

Түгээх хүчний трансформатор

| Model | Rated capacity (kVA) | HV (kV A) | HV tap (%) | LV (kV) | Linking group label | Impedance voltage (%) | Gross weight (t) | Dimensions (mm) L*W*H | No-load loss (W) | On-load loss (W) |
|--------------------|----------------------|------------------------|--------------------|---------|---------------------|-----------------------|------------------|-----------------------|------------------|------------------|
| S11-30/10 | 30 | 6 6.3 10 10.5 | ±2x 2.5% ±5% | 0.4 | Dyn11 Yyn0 | 4 | 0.35 | 750*480*800 | 80 | 630/600 |
| S11-50/10 | 50 | | | | | | 0.4 | 800*530*850 | 100 | 910/870 |
| S11-63/10 | 63 | | | | | | 0.42 | 950*650*880 | 110 | 1090/1040 |
| S11-80/10 | 80 | | | | | | 0.45 | 1000*720*920 | 130 | 1310/1250 |
| S11-100/10 | 100 | | | | | | 0.5 | 1000*750*950 | 150 | 1580/1500 |
| S11-125/10 | 125 | | | | | | 0.6 | 1050*750*970 | 170 | 1890/1800 |
| S11-160/10 | 160 | | | | | | 0.7 | 1120*770*1000 | 200 | 2310/2200 |
| S11-200/10 | 200 | | | | | | 0.8 | 1200*850*1020 | 240 | 2730/2600 |
| S11-250/10 | 250 | | | | | | 0.95 | 1350*950*1050 | 290 | 3200/3050 |
| S11-315/10 | 315 | | | | | | 1.1 | 1480*1000*1080 | 340 | 3830/3650 |
| S11-400/10 | 400 | | | | | | 1.25 | 1530*1050*1100 | 410 | 4520/4300 |
| S11-500/10 | 500 | | | | | | 1.45 | 1530*1100*1170 | 480 | 5410/5150 |
| S11-630/10 | 630 | | | | | | 1.75 | 1500*1050*1250 | 570 | 6200 |
| S11-800/10 | 800 | | | | | 2.0 | 1600*1180*1410 | 700 | 7500 | |
| S11-1000/10 | 1000 | | | | | 4.5 | 2.4 | 1750*1300*1500 | 830 | 10300 |
| S11-1250/10 | 1250 | | | | | | 3.0 | 1850*1420*1650 | 970 | 12000 |
| S11-1600/10 | 1600 | | | | | | 3.7 | 1950*1480*1720 | 1170 | 14500 |
| S11-2000/10 | 2000 | | | | | 5 | 4.5 | 2000*1510*1800 | 1390 | 18300 |
| S11-2500/10 | 2500 | | | | | | 5.2 | 2120*1620*1880 | 1650 | 21200 |